

REPAIRS HOLES AND CRACKS IN ALL HVAC/R TUBING AND PIPES

Tested to 1800 psi contained air or refrigeration pressure

Instant HVAC/R Patch is the combination of high strength bonding fluid and specialized bonding cells. The bonding fluid has an affinity for the bonding cells and when the two are combined, they form a high strength bond similar to a "weld" that permanently seals holes and cracks in all types of pipe and materials used in the HVAC/R industry.



Includes: Complete Bilingual Instructions.

- 1- Multi-functional Applications Tool
- 1- Part "A" Bonding Fluid with Application Tip
- 1- Part "B" Bonding Cells with Application Tip
- 2- Precision Application Brushes
- 1-60 Grit Sanding Patch

Repairs lines, drains, coils, in copper, aluminum, stainless steel, iron, PVC, CPVC, ridgid plastics, and much more.



HGHSIDE CHEMICALS INC.

• Works on Aluminum.

- Compatible with all refrigerant oils.
- For use on 410 systems.
- For use on coils and lines.
- Repairs leaks

Easy as: A + B + A

STEP 1

After sanding, apply BONDING FLUID (A) to repair area

STEP 2

Apply BONDING CELLS (B) on top of (A)

STEP 3

Apply BONDING FLUID (A) on top of (B)

SPECIFICATIONS:

- Holds 1800 psi contained pressure
- -60°F (51°C) to 200°F (93°C)
- Shore D 85+ hardness
- WARNING! DO NOT INGEST. BONDS SKIN AND EYES IN
- Non-toxic and safe to use on all potable SECONDS.
 water systems.

CAUTION: KEEP OUT OF REACH OF CHILDREN Read Instructions and Cautions inside package before using. Warranty limited to replacement of product.

11114 Reichold Road, Gulfport, MS 39503 U.S.A. 1-800-359-5599 1-228-896-9220 www.highsidechem.com

Making the Best Chemical Tools for Over 80 Years

